



Data Sheet

Seagull Netting 75 mm No-Flame

No-Flame Bird Netting is a high-performance solution designed for durability and longevity in environments where fire safety is an important consideration. Made from UV-stabilised, high-density polyethylene fibres, it resists weather extremes, insects, bacteria and fungi. Chemically inert and resistant to a wide range of temperatures, the netting offers a lifespan of 8–10 years when properly installed.

Its knotted mesh construction provides strength and durability, while the distinctive red identification strand allows easy recognition of its No-Flame properties.

Unlike standard bird control products, this No-Flame netting meets UL-94 V2 flammability standards, making it suitable for locations with strict fire-safety regulations. When exposed to flames, the material shrinks away rather than dripping molten plastic, helping to reduce fire spread and debris.

Material	100% Virgin HDPE
Colour	Black & Red
Mesh Size	Square mesh 75mm Sq. /100mm Str.
Weight	20.4g/sqm
Fibre Thickness	12/1000" (600 Denier / 0.30 mm)
Twine Designation	12/9 Ply
Twists	410–430 per metre
Flammability	PassNFPA701Method2
UV Protection	1000 Kly
Life Span	8-10 years
Break Strength (twine)	245N
Break Strength (35cm x 35cm)	756N

PERFORMANCE REQUIREMENT: BS 5867-2: 2008 Type B – Flammability requirements specification – Fabrics for curtains, drapes and window blinds.

TEST METHOD: BS EN ISO 15025: 2002 Procedure A (Surface Ignition) – Protective clothing – Protection against heat and flame. Methods of test for limited flame spread.



Unit 1-3 Cedar Park
30 Terminus Road
Chichester, West Sussex
PO19 8GT



01903 538 488



sales@pestfix.co.uk



www.pestfix.co.uk