



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes Date:** 16-Dec-2020

**Revision date** 24-Sep-2021  
**Revision Number** 4

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** EVO-STIK GRIPFILL ADHESIVE  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Adhesive.  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

**Company Name**  
Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650  
**Ireland** +353 (1) 8624900 (Monday- Friday 9am-5pm)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

<b>Skin corrosion/irritation</b>	Category 2 - (H315)
<b>Serious eye damage/eye irritation</b>	Category 2 - (H319)
<b>Chronic aquatic toxicity</b>	Category 3 - (H412)
<b>Flammable liquids</b>	Category 2 - (H225)

### 2.2. Label elements



**Signal word**  
Danger

### Hazard statements

H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H412 - Harmful to aquatic life with long lasting effects.  
H225 - Highly flammable liquid and vapour.

### Precautionary Statements - EU (§28, 1272/2008)

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233 - Keep container tightly closed  
P264 - Wash face, hands and any exposed skin thoroughly after handling  
P273 - Avoid release to the environment  
P280 - Wear protective gloves and eye/face protection  
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P337 + P313 - If eye irritation persists: Get medical advice/attention  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P501 - Dispose of contents/ container to an approved waste disposal plant

## Additional information

Placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

## 2.3. Other hazards

Harmful to aquatic life. In use, may form flammable/explosive vapour-air mixture.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Xylenes (o-, m-, p-isomers)	215-535-7	1330-20-7	5 - <10	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226) Aquatic Chronic 3 (H412)		01-2119488216-32-XXXX
Acetone	200-662-2	67-64-1	5 - <10	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336)		01-2119471330-49-XXXX

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes Date:** 16-Dec-2020

**Revision date** 24-Sep-2021  
**Revision Number** 4

				Flam. Liq. 2 (H225)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	64742-49-0	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)		01-2119475515-33-xxxx
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	64742-49-0	1 - <5	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)		01-2119484651-34-XXXX
Ethylbenzene	202-849-4	100-41-4	1- <2.5	STOT RE 2 (H373) Asp. Tox. 1 (H304) Acute Tox. 4 (H332) Flam Liq. 2 (H225) Aquatic Chronic 3 (H412)		01-2119489370-35-XXXX
Titanium dioxide	236-675-5	13463-67-7	0.01 - <0.1	Carc. 2 (H351) i		01-2119489379-17-XXXX

## **Full text of H- and EUH-phrases: see section 16**

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation.
----------	---

## 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
-----------------	------------------------

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray. Alcohol resistant foam.
------------------------------	---

Unsuitable extinguishing media	No information available.
--------------------------------	---------------------------

### 5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
--	---

Hazardous combustion products	Carbon oxides. Carbon dioxide (CO <sub>2</sub> ). Silicon dioxide.
-------------------------------	--

### 5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
--	--

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
----------------------	--

Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
-------------------	--

For emergency responders	Use personal protection recommended in Section 8.
--------------------------	---

### 6.2. Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
---------------------------	--

### 6.3. Methods and material for containment and cleaning up

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supercedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

- Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
- Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
- Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Advice on safe handling** Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.
- General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.
- Recommended storage temperature** Keep at temperatures between 5 and 25 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Adhesive.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	United Kingdom
Kaolin	-	TWA: 2 mg/m <sup>3</sup>

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes Date:** 16-Dec-2020

**Revision date** 24-Sep-2021  
**Revision Number** 4

1332-58-7		STEL: 6 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm TWA: 221 mg/m <sup>3</sup> STEL: 100 ppm STEL: 442 mg/m <sup>3</sup> *	TWA: 50 ppm TWA: 220 mg/m <sup>3</sup> STEL: 100 ppm STEL: 441 mg/m <sup>3</sup> Sk*
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup>	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup> STEL: 1500 ppm STEL: 3620 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 442 mg/m <sup>3</sup> STEL: 200 ppm STEL: 884 mg/m <sup>3</sup> *	TWA: 100 ppm TWA: 441 mg/m <sup>3</sup> STEL: 125 ppm STEL: 552 mg/m <sup>3</sup> Sk*

Chemical name	European Union	Ireland	United Kingdom
Xylenes (o-, m-, p- isomers) 1330-20-7	-	1.5 g/g Creatinine (urine - Methylhippuric acids end of shift)	650 mmol/mol creatinine urine
Acetone 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-
Ethylbenzene 100-41-4	-	0.7 g/g Creatinine (urine - sum of Mandelic acid and Phenylglyoxylic acid end of shift at end of workweek) 0.7 g (end-exhaled air - not critical)	-

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Xylenes (o-, m-, p- isomers) (1330-20-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	180 mg/kg bw/d	
Long term Systemic health effects worker	Inhalation	77 mg/m <sup>3</sup>	
Short term Local health effects Systemic health effects worker	Inhalation	289 mg/m <sup>3</sup>	

Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Inhalation	1210 mg/m <sup>3</sup>	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term	Inhalation	2085 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes Date:** 16-Dec-2020

**Revision date** 24-Sep-2021  
**Revision Number** 4

Systemic health effects worker Long term Systemic health effects	Dermal	300 mg/kg bw/d	
---	--------	----------------	--

<b>Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane (64742-49-0)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Dermal	13964 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	2085 mg/m <sup>3</sup>	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

<b>Derived No Effect Level (DNEL)</b>			
<b>Acetone (67-64-1)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

<b>Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	447 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

<b>Eye/face protection</b>	Tight sealing safety goggles. Face protection shield.
<b>Hand protection</b>	Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
<b>Skin and body protection</b>	Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Liquid
<b>Colour</b>	No information available
<b>Odour</b>	Solvent
<b>Odour threshold</b>	No information available

Property	Values	Remarks • Method
<b>pH</b>	No data available	Not applicable Insoluble in water
<b>pH (as aqueous solution)</b>	No data available	
<b>Melting point / freezing point</b>	No data available	
<b>Initial boiling point and boiling range</b>	= 60 °C	
<b>Flash point</b>	-10 °C	
<b>Evaporation rate</b>	No data available	
<b>Flammability</b>	Not applicable for liquids .	
<b>Flammability Limit in Air</b>		
<b>Upper flammability or explosive</b>	No data available	



# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

limits	
Lower flammability or explosive limits	No data available
Vapour pressure	No data available
Relative vapour density	No data available
Relative density	No data available
Water solubility	No data available
Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	500 mm <sup>2</sup> /s @ 40°C
Dynamic viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available

## 9.2. Other information

Solid content (%)	No information available
VOC Content (%)	
Liquid Density	1.18

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

### 10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

### Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None under normal processing.
------------------------------------	-------------------------------

### 10.4. Conditions to avoid

Conditions to avoid	Heat, flames and sparks.
---------------------	--------------------------

### 10.5. Incompatible materials

Incompatible materials	Strong acids. Strong bases. Strong oxidising agents.
------------------------	--

### 10.6. Hazardous decomposition products

Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.
----------------------------------	--

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

## Information on likely routes of exposure

### Product Information

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. May cause redness and tearing of the eyes.

## Numerical measures of toxicity

### Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (dermal)</b>	10,919.10 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	13.10 mg/l
<b>ATEmix (inhalation-vapour)</b>	104.90 mg/l

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylenes (o-, m-, p- isomers) 1330-20-7	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	=>47635 mg/L (Rattus) 4 h = >5000 ppm (Rattus) 4 h
Acetone 67-64-1	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m <sup>3</sup> (vapour) (rat OECD 403)
Ethylbenzene 100-41-4	=3500 mg/kg (Rattus)	= 15400 mg/kg (Oryctolagus cuniculus)	=17.4 mg/L (Rattus) 4 h
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	Classification based on data available for ingredients. Irritating to skin.
<b>Serious eye damage/eye irritation</b>	Classification based on data available for ingredients. Causes serious eye irritation.
<b>Respiratory or skin sensitisation</b>	Based on available data, the classification criteria are not met.
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

**Carcinogenicity** Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide 13463-67-7	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Xylenes (o-, m-, p-isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss ) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (Daphnia magna)		
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss )	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	ErL50 (72h) = 10-30 mg/L (Pseudokirchneriella subcapitata)	LL50 (96h) >13.4 mg/L (Oncorhynchus mykiss) OECD 203	-	EL50 (48h) = 3.0 mg/L (Daphnia magna)		
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EL50 (72h) = 13.6 mg/l (Pseudokirchneriella subcapitata)	LL50 (96h) = 18.27 mg/l (Oncorhynchus mykiss)	-	EL50 (48h)= 31.9 mg/l (Daphnia magna)		

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes Date:** 16-Dec-2020

**Revision date** 24-Sep-2021  
**Revision Number** 4

64742-49-0	iella subcapitata)	mykiss)		magna)		
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Component Information			
Xylenes (o-, m-, p- isomers) (1330-20-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	biodegradation	87.8 % Readily biodegradable

Acetone (67-64-1)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	98%	Readily biodegradable

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

### Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15	15
Acetone 67-64-1	-0.24	0.69
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	3.6	501
Ethylbenzene 100-41-4	3.2	15

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Xylenes (o-, m-, p- isomers) 1330-20-7	The substance is not PBT / vPvB
Acetone 67-64-1	The substance is not PBT / vPvB
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	The substance is not PBT / vPvB
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	The substance is not PBT / vPvB
Ethylbenzene 100-41-4	The substance is not PBT / vPvB
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply

## 12.6. Other adverse effects

**Other adverse effects** No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
<b>Contaminated packaging</b>	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
<b>European Waste Catalogue</b>	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

### Land transport (ADR/RID)

<b>14.1 UN number or ID number</b>	UN1133
<b>14.2 Proper Shipping Name</b>	Adhesives
<b>14.3 Transport hazard class(es)</b>	3
<b>Labels</b>	3
<b>14.4 Packing group</b>	II
<b>Description</b>	UN1133, Adhesives, 3, II, (D/E)
<b>14.5 Environmental hazards</b>	Not applicable
<b>14.6 Special Provisions</b>	640C
<b>Classification code</b>	F1
<b>Tunnel restriction code</b>	(D/E)
<b>Limited Quantity (LQ)</b>	5 L
<b>ADR Hazard Id (Kemmler Number)</b>	33

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

## IMDG

14.1 UN number or ID number	UN1133	
14.2 Proper Shipping Name	Adhesives	
14.3 Transport hazard class(es)	3	
14.4 Packing group	II	
Description	UN1133, Adhesives, 3, II, (-10°C c.c.)	
14.5 Marine pollutant	NP	
14.6 Special Provisions	None	
Limited Quantity (LQ)	5 L	
EmS-No	F-E, S-D	
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code		Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A3
Limited Quantity (LQ)	1 L
ERG Code	3L

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	28. 29. 75.
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	28. 29. 75.

### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

# SAFETY DATA SHEET

EVO-STIK GRIPFILL ADHESIVE  
Supersedes Date: 16-Dec-2020

Revision date 24-Sep-2021  
Revision Number 4

## Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product contains

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted
Acetone - 67-64-1	X	

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

#### Legend

TWA

TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling

Ceiling Limit Value

\*

Skin designation

SVHC

Substance(s) of Very High Concern

PBT

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB

Very Persistent and very Bioaccumulative (vPvB) Chemicals

# SAFETY DATA SHEET

**EVO-STIK GRIPFILL ADHESIVE**  
**Supersedes Date:** 16-Dec-2020

**Revision date** 24-Sep-2021  
**Revision Number** 4

---

STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

## **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 24-Sep-2021

## **Indication of changes**

**Revision note** SDS sections updated: 3.

**Training Advice** Provide adequate information, instruction, and training for operator

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**