T2031

Page: 1

Compilation date: 13/05/2020

Revision No: 2

Section 1: Identification of the subs	stance/mixture and of the company/undertaking
1.1. Product identifier	
Product name:	T2031
Product code:	T2031
1.2. Relevant identified uses o	f the substance or mixture and uses advised against
1.3. Details of the supplier of t	he safety data sheet
Company name:	
	K4 Business Centre
	131 Cambuslang Road,
	Glasgow,
	G31 8NB
	Tel: 0800 4582 435
	Email: info@medik4l.uk
1.4. Emergency telephone nun	nber
Emergency tel:	0800 4582 435
	(office hours only)
Section 2: Hazards identification	
2.1. Classification of the substa	ance or mixture
	Aquatic Chronic 3: H412; Flam. Aerosol 1: H222; -: H229
Most important adverse effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful to
	aquatic life with long lasting effects.
2.2. Label elements	
Label elements:	
Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated.
	H412: Harmful to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame
	$\mathbf{\vee}$
Signal words:	Danger

MEDIK4N

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing spray.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501: Dispose of contents/container to hazardous or special waste collection point.

Haz. ingredients (label): ETHANOL; BUTANE; PROPANE; ISOBUTANE

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHANOL - REACH registered number(s): 01-2119457610-43

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	30-50%

BUTANE

203-448-7	106-97-8	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	10-30%
		workplace exposure limit.		

PROPANE

200-827-9	74-98-6	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	10-30%
		workplace exposure limit.		

ISOBUTANE

200-857-2	75-28-5	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	10-30%
		workplace exposure limit.		

3-IODO-2-PROPYNYL BUTYLCARBAMATE

259-627-5	55406-53-6	-	Acute Tox. 3: H331; Acute Tox. 4: H302;	<1%	
			STOT RE 1: H372; Eye Dam. 1: H318; Skin		
			Sens. 1: H317; Aquatic Acute 1: H400;		
			Aquatic Chronic 1: H410		

Non-classified ingredients:

DIDECYLDIMETHYLAMMONIUM CHLORIDE - REACH registered number(s): 01-2119945987-15

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
230-525-2	7173-51-5	-	Acute Tox. 4: H302; Skin Corr. 1B: H314	<1%	

Section 4: First aid measures

MEDIK4N

		Page:	3
4.1. Description of first aid me	asures		
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash		
	immediately with plenty of soap and water.		
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.		
Ingestion:	Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of		
	water to drink immediately. Consult a doctor.		
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious	,	
	ensure the casualty sits or lies down. Move to fresh air in case of accidental inhalation		
	of vapours. Consult a doctor.		
4.2. Most important symptom	s and effects, both acute and delayed		
Skin contact:	There may be mild irritation at the site of contact.		
Eye contact:	There may be irritation and redness. The eyes may water profusely.		
Ingestion:	There may be difficulty swallowing. Headaches or general malaise may result. There		
	may be vomiting and diarrhoea. The casualty may appear intoxicated. There may be los	s	
	of consciousness.		
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure		
	may cause coughing or wheezing. Drowsiness or mental confusion may occur. There may	ıy	
	be loss of consciousness.		
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.		
4.3. Indication of any immedia	te medical attention and special treatment needed		
Section 5: Fire-fighting measures			
5.1. Extinguishing media			
Extinguishing media:	Use water spray to cool containers. Suitable extinguishing media for the surrounding		
	fire should be used.		
5.2. Special hazards arising fro	m the substance or mixture		
Exposure hazards:	Extremely flammable. In combustion emits toxic fumes. Fire exposed aerosols should be	5	
	sprayed with water to reduce risk of rupture/explosion. Contents of aerosol will add to		
	fuelling of fire.		
5.3. Advice for fire-fighters			
Advice for fire-fighters:	Wear self-contained breathing apparatus.		
Section 6: Accidental release meas	ures		
6.1. Personal precautions, pro	tective equipment and emergency procedures		
Personal precautions:	Do not attempt to take action without suitable protective clothing - see section 8 of SD	5.	
	Eliminate all sources of ignition. If outside keep bystanders upwind and away from		

danger point.

6.2. Environmental precautions

MEDIK4N

Page: 4

	•	Do not discharge into drains or rivers.			
6.3. M	ethods and material for c	ontainment and cleaning up			
	Clean-up procedures: (Clean-up should be dealt with only by	qualified personnel familia	ar with the specific	
	2	ubstance. Refer to section 13 of SDS f	for suitable method of disp	oosal.	
6.4. Re	eference to other sections				
Refe	rence to other sections:	Refer to section 8 of SDS.			
Section 7: Ha	ndling and storage				
7.1. Pr	ecautions for safe handlir	g			
	Handling requirements:	nsure there is sufficient ventilation of	f the area. Avoid direct co	ntact with the substance	
		smoking is forbidden.			
7.2. Conditions for safe storage, including any incompatibilities					
Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away				ignition. Keen away	
		rom direct sunlight.		Sincer weep away	
	Suitable packaging:	-			
7.3. Sp	pecific end use(s)				
Section 8: Exp	posure controls/person	al protection			
Hazardous ingree ETHANOL Workplace expo	dients:				
State	sure limits:	Res	spirable dust:		
	sure limits: 8 hour TWA		spirable dust:	15 min. STEL	
UK		15 min. STEL	-	15 min. STEL	
UK BUTANE	8 hour TWA	15 min. STEL	8 hour TWA		
	8 hour TWA	15 min. STEL 13 -	8 hour TWA		
BUTANE	8 hour TWA 1920 mg/n	15 min. STEL 13 -	8 hour TWA		
BUTANE UK	8 hour TWA 1920 mg/n	15 min. STEL 13 - 13 1810 mg/m3	8 hour TWA		
BUTANE UK PROPANE	8 hour TWA 1920 mg/n 1450 mg/n	15 min. STEL 13 - 13 1810 mg/m3	8 hour TWA		
BUTANE UK PROPANE UK	8 hour TWA 1920 mg/n 1450 mg/n	15 min. STEL 13 - 13 1810 mg/m3 13 7200 mg/m3	8 hour TWA	·	
BUTANE UK PROPANE UK ISOBUTANE UK	8 hour TWA 1920 mg/m 1450 mg/m 1800 mg/m 2400 mg/m	15 min. STEL 13 - 13 1810 mg/m3 13 7200 mg/m3	8 hour TWA	·	
BUTANE UK PROPANE UK ISOBUTANE UK	8 hour TWA 1920 mg/m 1450 mg/m 1800 mg/m 2400 mg/m	15 min. STEL 13 13 13 1810 mg/m3 13 7200 mg/m3 13 9600 mg/m3	8 hour TWA	·	
BUTANE UK PROPANE UK ISOBUTANE UK DNEL/	8 hour TWA 1920 mg/m 1450 mg/m 1800 mg/m 2400 mg/m PNEC Values DNEL / PNEC m	15 min. STEL 13 - 13 1810 mg/m3 13 7200 mg/m3	8 hour TWA	·	
BUTANE UK PROPANE UK ISOBUTANE UK DNEL/	8 hour TWA 1920 mg/m 1450 mg/m 1800 mg/m 2400 mg/m PNEC Values DNEL / PNEC m sposure controls	15 min. STEL 13 13 13 1810 mg/m3 13 7200 mg/m3 13 9600 mg/m3	8 hour TWA	·	

equipment are not a source of ignition.

MEDIK4N

Page: 5

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol		
Colour:	Colourless		
Odour:	Pleasant		
Evaporation rate:	Fast		
Oxidising:	Not applicable.		
Solubility in water:	Slightly soluble		
Also soluble in:	Most organic solvents.		
Viscosity:	Non-viscous		
Boiling point/range°C:	<100	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	-20 Pa	rt.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	Not applicable.	pH:	Not applicable.
VOC g/l:	No data available.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases. Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

MEDIK4N

Page: 6

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

DERMAL	RBT	LD50	>2000	mg/kg
ORL	MUS	1H LC50	>20	mg/kg
ORL	RAT	LD50	>2000	mg/kg

Non-classified ingredients:

DIDECYLDIMETHYLAMMONIUM CHLORIDE

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	658	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposur	e
Skin contact:	There may be mild irritation at the site of contact.
Skii contact.	There may be mild initiation at the site of contact.
Eye contact:	There may be irritation and redness. The eyes may water profusely.
Ingestion:	There may be difficulty swallowing. Headaches or general malaise may result. There
	may be vomiting and diarrhoea. The casualty may appear intoxicated. There may be loss
	of consciousness.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure
	may cause coughing or wheezing. Drowsiness or mental confusion may occur. There may
	be loss of consciousness.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ETHANOL

ALGAE	48H EC50	>100	mg/l
Daphnia magna	48H EC50	>100	mg/l
FISH	96H LC50	>100	mg/l

DIDECYLDIMETHYLAMMONIUM CHLORIDE

DAPHNIA	48H EC50	0.06	mg/l
GREEN ALGA (Selenastrum capricornutum)	48H EC50	0.12	mg/l

MEDIK4N

			Page: 7
ZEBRAFISH (Brachydanio rerio)	96H LC50	0.97	mg/l
12.2. Persistence and degradal	bility		
Persistence and degradability:	Biodegradable.		
12.3. Bioaccumulative potentia	al		
Bioaccumulative potential:	No bioaccumulation potential.		
12.4. Mobility in soil			
Mobility:	Soluble in water.		
12.5. Results of PBT and vPvB a	assessment		
PBT identification:	This product is not identified as a PBT/vPvB	substance.	
12.6. Other adverse effects			
Other adverse effects:	Harmful to aquatic organisms.		
Section 13: Disposal considerations			
13.1. Waste treatment method	ds		
Disposal operations:	Transfer to a suitable container and arrange	for collection by specialise	d disposal
	company.		
NB:	The user's attention is drawn to the possible regulations regarding disposal.	e existence of regional or na	ational
Section 14: Transport information			
14.1. UN number			
UN number: 14.2. UN proper shipping name			
Shipping name: 14.3. Transport hazard class(es			
Transport class:			
14.4. Packing group	2		
14.5. Environmental hazards			
	N-	Marine	
Environmentally hazardous: 14.6. Special precautions for u		marine p	ollutant: No
	Limited Quantity - 1 Litre/Kilo		
Tunnel code:			
Transport category:	2		
Section 15: Regulatory information			

MEDIK4N

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H220: Extremely flammable gas.
	H222: Extremely flammable aerosol.
	H225: Highly flammable liquid and vapour.
	H229: Pressurised container: May burst if heated.
	H302: Harmful if swallowed.
	H314: Causes severe skin burns and eye damage.
	H317: May cause an allergic skin reaction.
	H318: Causes serious eye damage.
	H331: Toxic if inhaled.
	H372: Causes damage to organs through prolonged or repeated exposure.
	H400: Very toxic to aquatic life.
	H410: Very toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.