

PEST PROOFING SOLUTIONS FOR ALL TYPES OF ENTRANCE SYSTEMS AND BUILDING COMPONENTS!

RAXIT SEALS' UNIQUE PATENTED TECHNOLOGY

The Raxit Seals pest proofing products are developed in the flexible and extremely durable rubber material Santoprene™. Along the length of the Raxit Seals are 1mm inlaid acid resistant stainless steel wires, which makes the seals impossible for rodents to gnaw through. The Raxit Seals have undergone – and successfully passed - the **toughest tests** for rodent penetration and general durability for any sweeps in the market. Making Raxit Seals the safest choice!

IMPORTANT: All Raxit Seals have a waved/corrugated surface which prevents the inlaid steelwires from sliding.



RAXIT READY-TO-USE -FEATURES AND BENEFITS

- A versatile product which can be used to solve most pest proofing task.
- The Raxit Seals' inlaid steel wires are developed so that the seal will return to its original shape, after deformation. Useful in entrance settings with uneven terrain.
- High cost effectiveness compared to alternative products due to: moderate pricing, easy and laborsaving installation and long durability.
- Successfully passed the toughest accredited tests for rat and mice penetration (respectively for rats 14 days and mice 70 days).
- Successfully passed accredited tests that concluded the Raxit Seals as a great climate barrier and water intrusion barrier.
- All materials used are non-toxic, the seal's color does not spread on surfaces and easy to clean (can be high pressure washed).
- Insect barrier at the bottom of the seal which ensures the Raxit Seal can fit closely to terrain. prevents small insects to pass under the seal.
- Professionally packed with an easy-to-understand mounting guide inside the packaging.
- Review the Raxit Seal periodically for gnawmarks, or other damages. Contact your Pest Control Operator as required.

BEST IN TEST

PRODUCT SPECIFICATIONS

- **Seal length** - 1 meter and 3 meter.
- **Seal height** - 20mm, 30mm and 40mm.
- **Weight** - 380 gram /meter.
- **Seal color** - Anthracite gray (more colors available upon request).
- **Aluminum color** - Natural and RAL 9005 (more colors available upon request).
- **Distance between bottom edge and first steel wire** - 3mm i.e. too little for a mice to squeeze through.
- **Distance between inlaid steel wires** - 5mm.
- **Temperature range** - -40 celsius to 60 celsius.
- **Shore A hardness** - Around 80.
- **Thermal expansion and contraction** - Insignificant.

