

## PEST PROOFING SOLUTIONS FOR ALL TYPES OF ENTRANCE SYSTEMS AND BUILDING COMPONENTS!

### ➔ RAXIT SEALS' UNIQUE PATENTED TECHNOLOGY

The Raxit Seals pest proofing products are developed in the flexible and extremely durable rubber material Santoprene™. Along the length of the Raxit Seals are 1mm inlaid acid resistant stainless steel wires, which makes the seals impossible for rodents to gnaw through. The Raxit Seals have undergone – and successfully passed - the **toughest tests** for rodent penetration and general durability for any sweeps in the market. Making Raxit Seals the safest choice!

**IMPORTANT:** All Raxit Seals have a waved/corrugated surface which prevents the inlaid steelwires from sliding.



### ➔ RAXIT SEAL - FEATURES AND BENEFITS

**BEST IN TEST**

- A versatile product which can be used to solve most pest proofing task.
- The Raxit Seals' inlaid steel wires are developed so that the seal will return to its original shape, after deformation. Useful in entrance settings with uneven terrain.
- High cost effectiveness compared to alternative products due to: moderate pricing, easy and laborsaving installation, long durability, minimal trimming waste when cutting according to your measurements from a roll.
- Successfully passed the toughest accredited tests for rat and mice penetration (respectively for rats 14 days and mice 70 days).
- Successfully passed accredited tests that concluded the Raxit Seals as a great climate barrier and water intrusion barrier.
- The Raxit Seal are available in rolls of up to 25 meter, despite its length of 25 meter, the rolls are compact which ensures; easy handling, storing and transportation.
- All materials used are non-toxic, the seal's color does not spread on surfaces and easy to clean (can be high pressure washed).
- Insect barrier at the bottom of the seal which ensures the Raxit Seal can fit closely to terrain. prevents small insects to pass under the seal.
- Review the Raxit Seal periodically for gnawmarks, or other damages. Contact your Pest Control Operator as required.

### ➔ PRODUCT SPECIFICATIONS

- **Seal length** - 1-25 meter.
- **Seal height** - 75mm & 110mm.
- **Seal thickness** - 3,8mm.
- **Weight** - 300 & 420 gram /meter.
- **Seal color** - Anthracite gray (more colors available upon request).
- **Distance between bottom edge and first steel wire** - 3mm i.e. too little for a mice to squeeze through.
- **Distance between inlaid steel wires** - 5mm.
- **Temperature range** - -40 celsius to 60 celsius.
- **Shore A hardness** - Around 80.
- **Thermal expansion and contraction** - Insignificant.

