

SAFETY DATA SHEET
BISLEY GUN OIL AEROSOL

Issue No. 4

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: BISLEY Gun Oil Aerosol

Company name: John Rothery (Wholesale) Ltd
Rothery House
Waterberry Drive
Waterlooville
PO7 7XX
United Kingdom
Tel: +44 (0)2392 245350
Fax: +44 (0)2392 245351
Emergency Tel: +44 (0)2392 245350

2. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Repeated exposure may cause skin dryness or cracking. May cause long term adverse effects in the aquatic environment.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: Butane 1-10% EINECS: 203-448-7 CAS: 106-97-8 [F+] R12

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely

Ingestion: There may be irritation of the throat and mouth.

Inhalation: Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: DO NOT induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

SAFETY DATA SHEET
BISLEY GUN OIL AEROSOL

Issue No. 4

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

7. HANDLING AND STORAGE

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: BUTANE

WEL (8 hr TWA): 1450 mg/m³ WEL (15 min STEL): 1810 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Boiling point /range°C: - 2 to -45

Flash point°C: -10

10. STABILITY AND REACTIVITY

SAFETY DATA SHEET
BISLEY GUN OIL AEROSOL

Issue No. 4

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: Product is bioaccumulative, but with a short retention period of the order of one week.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SAFETY DATA SHEET
BISLEY GUN OIL AEROSOL

Issue No. 4

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1950

ADR Class: 2

Classification code: 5F

Shipping name: AEROSOLS

Labelling: 2.1



IMDG / IMO

UN no: 1950

Class: 2

EmS: F-D,S-U

Marine pollutant: Yes

Labelling: 2.1

IATA / ICAO

UN no: 1950

Class: 2.1

Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.



Risk phrases:

R12: Extremely flammable.

Safety phrases:

S2: Keep out of the reach of children.

S46: If swallowed, seek medical advice immediately and show this container or label. S51: Use only in well-ventilated areas.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition.

No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

SAFETY DATA SHEET
BISLEY GUN OIL AEROSOL

Issue No. 4

16. OTHER INFORMATION

Risk phrases used in s.3: R12: Extremely flammable.

If you have purchased this product for supply, to a third party, for use at work it is your duty to take all necessary steps to ensure that any person handling or using the product is provided with the information within this sheet.

If you are an employer, it is your duty to tell your employees and others, that maybe affected by the hazards described in this sheet, of any precautions that should be taken.

Legislation and other sources have been used in the compilation of this safety data sheet.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product..

Issue 4

Dated 28/09/12