



Technical Specification

Non Piercing Rubber Roof Mounts

SKU: NF340 / NF365

Product Description

Durable, non-penetrative mounts for flat or membrane roofs. Made from UV-stable, recycled rubber, they provide secure ballast without drilling or damaging roof surfaces.

Each unit distributes load evenly, preventing leaks and preserving membrane integrity. Compatible with solar panels, conduits, and bird control systems, they install quickly and can be repositioned as needed.

Key Features:

- Non-piercing design protects roof membrane
- Recycled, UV-resistant rubber construction
- Even load distribution and vibration damping
- Quick installation and easy relocation

Material Specification

- SBR (Styrene Butadiene Rubber), recycled with a Polyurethane Pre-Polymer moisture curing bond. UV Stabilised.
- Environmentally friendly

Working Conditions

This product is suitable for both indoor and outdoor use, with a temperature tolerance range of -40°C to +80°C.

SKU	Base size (mm)	Core size (mm)	Key Height (mm)	Strut hole depth (mm)	Fixing Bolt Hole Diameter	Rec. Loading per Foot (kg)	Ballast Weight per Foot (kg)
NF340	350 x 350	41 x 41	100	60	M10	2,500	5.7
NF365	500 x 500	41 x 41	130	90	M10	4,000	13.9